

Compact workgroup productivity.

imageRUNNER
2520/i, 2525/i, 2530/i,
2535/i, 2545/i

you can

A RANGE OF SPEEDS FROM 20 TO
45 PPM / CPM, A3 BLACK-AND-WHITE

UP TO 2,300 SHEET PAPER CAPACITY

SEND DIRECT TO EMAIL AND
NETWORK FOLDER

5.7 INCH / 14.47 CM TOUCH
SCREEN DISPLAY

CLASS-LEADING ENERGY EFFICIENCY

COMPACT DESIGN

Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45 ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.



Productivity and efficiency

- Easy-to-use touch-screen display saves time
- Fast output speeds up to 45 ppm
- Send in colour to network folders or email in a variety of formats*
- Fewer interruptions with up to 2,300 sheet paper capacity
- Simple, hassle-free integration – Network ready, PCL* and optional PostScript Support
- Optional inner staple finisher
- e-Maintenance service provides remote diagnostics, automated meter readings and toner management.

Environmental

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output.

Cost-effective

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance.

Security

- Secure Print** keeps documents confidential during printing
- Department ID secures access to the device
- uniFLOW compatibility offers the flexibility and convenience of My Print Anywhere secure release with job selection.

* Standard on i models, optional on non i models
** RAM-based secure print for up to 100 jobs

imageRUNNER

Canon

Specifications: imageRUNNER 2500 Series

| | | |
|--|---|--|
| Type | Desktop or Free-standing (Reader-Printer Combined) | |
| Maximum Original Size | A3 | |
| Copy Sizes | Cassette 1, 3, 4 A3, A4, A4R, A5R. Custom size: 139.7 to 297mm x 182 to 432mm | |
| | Cassette 2 | A3, A4, A4R, A5R |
| | Stack Bypass | A3, A4, A4R, A5R |
| Resolution | Custom Size | 99 to 297mm x 148 to 432mm |
| | Reading | 600dpi x 600dpi |
| | Copying | 600dpi x 600dpi |
| | Printing | 600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only) |
| | No. of Tones | 256 Gradations |
| COPY/PRINT SPEED | | |
| | A4 | imageRUNNER 2545i / 2545: 45ppm (BW) imageRUNNER 2535i / 2535: 35ppm (BW) imageRUNNER 2530i / 2530: 30ppm (BW) imageRUNNER 2520i / 2520: 25ppm (BW) imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 22ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) imageRUNNER 2520i / 2520: 15ppm (BW) |
| | A3 | imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 15ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) |
| Magnification | Zoom | 25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400% |
| First Copy Time | Black & White | 3.9 sec (45 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model) |
| Warm-Up Time | Duplexing | 1 to 999 sheets |
| Multiple Copies/Prints | Duplexing | Standard |
| Paper Weight | Cassette | 64 to 90g/m ² ; Stack Bypass: 64 to 128g/m ² ; Duplex: 64 to 80g/m ² |
| Paper Capacity | Cassette 1 | 550 sheets (80g/m ²) (250 sheets for the imageRUNNER 2520i / 2520) |
| | Cassette 2 | 550 sheets for imageRUNNER 2525i, 2530i/i, 2535i/i, 2545i/i |
| | Stack Bypass | 100 sheets (A4, A4R, A5; 80g/m ²), 50 sheets (A3; 80g/m ²) |
| | Optional | 550 sheets x 2 cassettes (80g/m ²) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only |
| | Paper Deck | None |
| | Total Capacity | 2,300 sheets. (2,000 sheets for the imageRUNNER 2520i / 2520) Canon Custom Processor, 400MHz |
| CPU | Memory | 512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models) |
| Hard Disk Drive | Interface | None |
| | Power Supply | Ethernet (100Base-TX / 10Base-T), USB Host1 / F 2.0 x 1 port, USB Device 1.0 x 1 port |
| Max. Power Consumption | | 220-240V AC, 50/60Hz, 4.2A (45 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (30 / 25 / 20ppm model) |
| Dimensions (W x D x H) | | 1.827kW (45 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model) |
| | Weight | imageRUNNER 2545i / 2545 / 2535i / 2535: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520: 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF) imageRUNNER 2545i / 2535i: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg, imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg, imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg |
| PRINT SPECIFICATION | | |
| PDL | UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional) | |
| Resolution | 600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only) | |
| Memory | 512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models) | |
| Hard Disk | None | |
| CPU | Canon Custom Processor, 400MHz | |
| Fonts | PS Fonts: Roman 136, PCL Fonts: Roman 93 | |
| Supported OS | PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Postscript level 3 emulation: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later | |
| Interface | Ethernet (100Base-TX / 10Base-T) | |
| Network Protocol | TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support | |
| Pull Scan | Network TWIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White) | |
| SEND SPECIFICATION/ CLR SEND KIT-Y1 | | |
| (standard on i models, optional on non i models) | | |
| Scan Speed | 45 / 34ipm (45 / 35ppm model), 25 / 13ipm (30 / 25 / 20ppm model) | |
| Scan Resolution | BW | 100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi |
| | CL | 100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi |
| Destinations | E-Mail / Internet FAX (SMTP), PC / Server (SMB,FTP), USB memory keys | |
| Address Book | Local (Max. 500) | |
| File Format | TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1) | |

| | | |
|---|---|--|
| DADF-AA1 for imageRUNNER 2545/2535 | | |
| Paper Size | A3, A4, A4R, A5, A5R | |
| Paper Weight | Single sided original: 42 to 128g/m ² , Double sided original: 50 to 128g/m ² | |
| Max. Number of Originals | 100 sheets (A4, A4R, A5, A5R: 80g/m ²), 50 sheets (A3: 80g/m ²) | |
| Document Scanning Speed (max.) | Copy Scan | 45ipm (A4, 600 x 600dpi: BW) 45 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) |
| Dimensions (W x D x H) | 565 x 540 x 137mm | |
| Weight | Approx. 7.9kg | |
| DADF-AB1 for imageRUNNER 2530/2525/2520 | | |
| Paper Size | A3, A4, A4R, A5, A5R | |
| Paper Weight | Single sided original: 37 to 128g/m ² , Double sided original: 50 to 128g/m ² | |
| Max. Number of Originals | 50 sheets (A4, A4R, A5, A5R: 80g/m ²), 25 sheets (A3: 80g/m ²) | |
| Document Scanning Speed (max.) | Copy Scan | 25ipm (A4, 600 x 600dpi: BW) 25 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) |
| Dimensions (W x D x H) | 565 x 544 x 126mm | |
| Weight | Approx. 7.0kg | |
| CASSETTE UNIT-W1 for imageRUNNER 2520/i | | |
| Type | Front-loading adjustable drawers | |
| Paper Size | A3, A4, A4R, A5R | |
| Custom Size | 139.7 to 297mm x 182 to 432mm | |
| Paper Weight | 64 to 90g/m ² | |
| Paper Capacity | 550 sheets (80g/m ²) x 1 cassette | |
| Dimensions (W x D x H) | 565 x 680 x 97mm | |
| Weight | Approx. 12.8kg | |
| CST. FEEDING UNIT-AE1 for all models | | |
| Type | 2 Front-loading adjustable drawers | |
| Paper Size | A3, A4, A4R, A5R | |
| Custom Size | 139.7 to 297mm x 182 to 432mm | |
| Paper Weight | 64 to 90g/m ² | |
| Paper Capacity | 550 sheets (80g/m ²) x 2 cassettes | |
| Dimensions (W x D x H) | 565 x 680 x 248mm | |
| Weight | Approx. 24.0kg | |
| INNER FINISHER-B1 for all models | | |
| Number of Trays | One stack tray (Optional 2nd Tray: INNER FIN ADD. TRAY-B1) | |
| Tray Capacity | A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height) | |
| Staple Position | Corner, Double | |
| Staple Capacity | A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets | |
| Dimensions (W x D x H) | 416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended) | |
| Weight | Approx. 12.5kg | |
| INNER 2-WAY TRAY-G1 for all models | | |
| Number of Trays | 2 stack tray | |
| Tray Capacity | Tray A | A4: 250 sheets, A3: 100 sheets |
| | Tray B | A4: 100 sheets, A3: 50 sheets |
| Dimensions (W x D x H) | 426 x 413 x 109mm | |
| Weight | Approx. 0.6kg | |
| OTHER ACCESSORIES | | |
| Platen Cover Type P: for imageRUNNER 2525/2530 without DADF | | |
| Platen Cover Type Q: for imageRUNNER 2535/2545 without DADF | | |
| Stamp Ink Cartridge-C1 | | |
| Stamp Unit-B | | |
| ADF Access Handle-A1 | | |
| PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models | | |
| PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing. | | |
| Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology | | |
| Super G3 Fax Board-AG1: Add fax functionality | | |
| FL Cassette-A11: This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i | | |
| FL Cassette-AK1: This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1 | | |
| FL Cassette-AL1: This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i | | |
| allows you to swap paper sizes without changing the printer settings. Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only. | | |
| 2 Way Unit-B1: Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530. | | |
| Staple-J1: Staples for Inner Finisher-B1. Document Tray-J1: Handy tray that attaches to the side of the device. | | |
| Power Supply Unit-U1. | | |
| Card Reader Attachment-D3: Attachment kit for Card Reader-F1. | | |
| Canon Card Reader-F1: Physical card access system that limits system access to authorised users. | | |
| USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory. | | |
| CCV1 I/F Cable-A1: Interface Kit for Coin-Vender. | | |
| C-EXV33 TONER BK: Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i. | | |
| C-EXV32 TONER BK: Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i | | |
| Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. | | |



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English Edition 0163W635
01/12/v1
© Canon Europa N.V., 2012

Canon (UK) Ltd
Woodhatch
Reigate
Surrey
RH2 8BF
Tel.: 01737 220000
Fax: 01737 220022
canon.co.uk

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Tel.: 01 2052400
Fax: 01 2052525
canon.ie